

ISAFE MOBILE TABLET ZONE 1/21 IS940.1



\$6,974.00 GST included

SKU: 01-00940001-001-002 | **Categories:** [Intrinsically Safe](#), [Smartphone](#) |



GALLERY IMAGES



PRODUCT DESCRIPTION

The 10.1-inch 5G Android tablet for data communication in the process industry and in automation integrates seamlessly into the existing system landscape with 4G/5G campus networks or Wi-Fi 6. It is equipped with a powerful, IIoT-optimised chipset from Qualcomm® Technologies, Inc. Other highlights of the robust and easy-to-handle tablet include a 16-pin ISM interface, 12-pin ISM interface for Docking Station, Wi-Fi 6, Bluetooth 5.2 and NFC support, a replaceable, long-lasting battery, freely programmable buttons and main and front cameras.

Advantages

- Android™ operating system
- Processor with long-term support: Qualcomm® QCM6490 Octa Core
- Large memory with 8 GB RAM, 128 GB internal memory expandable with microSD memory up to 128 GB
- Clear 10.1" display with Corning® Gorilla® Glass 3rd generation
 - Replaceable, powerful battery
 - Camera on the front and back
- Wireless communications such as Wi-Fi®, Bluetooth®, Near Field Communication (NFC), GPS, A-GPS,

- Glonass, A-Glonass, Beidou, Galileo
- Programmable red key (e.g. for lone worker protection/SOS)
- Additional programmable side buttons (assignable via "Button App")
 - Mounting VESA 100
- Amplified loudspeaker for noisy work environments
 - Type of protection: IP68 waterproof/dustproof
 - MIL-STD-810H
- Can be used from -20 °C to +55 °C

Technical Features

Operating system	Android™ 14
Processor	Qualcomm® QCM6490 Octa Core
Memory	8 GB RAM 128 GB internal memory microSD to 128 GB
Frequencies	4G LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12 MFBI/B13/B14/B17/B20/B25/B26/B28A/B28B/B29/B30/B66/B71/B68 4G LTE-TDD: B38/B39/B40/B41/B42/B43/B48 5G NR: n1/n2/n3/n5/n7/n8/n12/n14/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
Dimensions	Size: 266,17 x 168,46 x 19,82 mm Weight: 1059 g
Display	10,1" (25,654 cm) Corning® Gorilla® Glass V3 usable with gloves
Battery	8160 mAh, 3,7 V replaceable
Camera	50 MP AF rear 5 MP FF front
Connectivity	Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/e/k/r/ax/v with hotspot Bluetooth® 5.2 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication

Types of protection

IP68 dust-/waterproof
MIL-STD 810H
Usable from -20 °C to +55 °C

Expand

Certifications



IECEx (International) approved
Ex ib IIC T4 Gb
Ex ib IIIC T135°C Db

What's in the box

- Tablet
- Battery
- Hand Strap
- i.safe PROTECTOR 2.0
- Power Adapter universal
- Display Protection Foil
 - Screwdriver
- Safety Instructions

Downloads

[Datasheet IS940.1](#)

[Operating Manual IS940.1](#)

[Safety Instructions IS940.1](#)

[IECEx IS940.1](#)

This product is suitable for operation with PoC communication via public or campus networks (4G or 5G) or Wi-Fi® in Ex-Zones as per IEC Ex Rating on the devices

5G tablets for explosion hazardous areas

YOU MAY ALSO LIKE...



**BARTEC SP9EX1
Smartphone**



**Pixavi Cam -
Intrinsically Safe
Camera - Silver
Bundle**