



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx EPS 19.0034X** Page 1 of 3 [Certificate history:](#)

Status: **Current** Issue No: 0

Date of Issue: **2019-12-20**

Applicant: **i.safe MOBILE GmbH**
i_Park Tauberfranken 10
97922 Lauda-Koenigshofen
Germany

Equipment: **IS930.1 Intrinsically safe industrial tablet**

Optional accessory:

Type of Protection: **intrinsic safety "i"**

Marking: **Ex ib IIC T4 Gb**
Ex ib IIIC T135°C Db IP6X

Approved for issue on behalf of the IECEx
Certification Body:

Holger Schaffer

Position:

Certification Manager

Signature:
(for printed version)

Date:

2020-01-07

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

Bureau Veritas Consumer Products Services Germany GmbH
Businesspark A96
86842 Türkheim
Germany





IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 19.0034X**

Page 2 of 3

Date of issue: 2019-12-20

Issue No: 0

Manufacturer: **i.safe MOBILE GmbH**
i_Park Tauberfranken 10
97922 Lauda-Koenigshofen
Germany

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/EPS/ExTR19.0032/00](#)

Quality Assessment Report:

[DE/EPS/QAR12.0003/07](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 19.0034X**

Page 3 of 3

Date of issue: **2019-12-20**

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The IS930.1 is the intrinsically safe and rugged industrial tablet for use in explosion hazardous areas of zone 1 and 21. The IS930.1 provides numerous technologies like 4G (LTE), NFC, GPS, Wi-Fi and Bluetooth LE. Equipped with an Android operating system, amplified loudspeaker and option keys, which allows the allocation of user specific functions or applications.

Electrical data:

Supply: The tablet IS930.1 has a fixed installed rechargeable Li-Ion battery $U_0 = 3.8 \text{ V}$ ($U_{0_max} = 4.2 \text{ V}$).

Interfaces: The opening of the interface covers in explosive atmospheres is not permitted.

Wired data connection and charging is only allowed outside ex-hazardous areas.

$U_m = 5.88 \text{ V}$, this is ensured by using the Docking Station DS930.1, the i.safe PROTECTOR cables or other accessories specified by i.safe MOBILE GmbH.

A commercially available SD card may be used in the corresponding slot in the hazardous area. The internal electrical capacity of the SD card is negligible.

SPECIFIC CONDITIONS OF USE: YES as shown below:

The battery may be charged outside explosion hazardous areas only.

The device must be protected against permanent UV light emission and high electrostatic charge processes.

The permitted ambient temperature range is -20°C to $+60^\circ\text{C}$.