

IS940.1



APPROVALS



ATEX approval: EX-Zone 1/21
II 2G Ex ib IIC T4 Gb
II 2D Ex ib IIIC T135°C Db



IECEx approval: EX-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db



NEC500 approval: requested Class I Div. 1 Groups A, B, C, D, T4 Class II Div. 1 Groups E, F, G, T155°C Class III



Japan-Ex approval: requested Ex ib IIC T4 Gb Ex ib IIIC T135°C Db

Further approvals: IA (South Africa) | PCEC (China) | INMETRO (Brazil)

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

Android™ 14
0
Qualcomm® QCM6490 Octa Core
8 GB RAM 128 GB internal memory microSD memory up to 512 GB
4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI/13/14/17/20/25/26/28A/28B/29/30/66/68/71 4G LTE-TDD: B38/39/40/41/42/43/48 5G NR: n1/n2/n3/n5/n7/n8/n12/n14/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
Size: 266,17 x 168,46 x 19,82 mm weight: 1059 g
10,1" (25,65 cm) Corning® Gorilla® Glass 3rd generation 1200 x 1920 pixels usable with gloves
8160 mAh replaceable
50 MP AF rear camera 5 MP FF front camera
1 nano SIM + eSIM
Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v Bluetooth® 5.2 GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo Near Field Communication (NFC)
16-pin ISM interface 12-pin ISM interface (Docking Station: optional accessory) USB-C
Accelerometer, Gyroscope, Light, Magnetic, Proximity, Pressure sensors
IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +55 °C

FURTHER FEATURES

FUNCTION KEY RED	Optional functions assignable via System App, e.g. LWP	
FUNCTION KEYS RIGHT	Optional functions assignable via Button App (system integrated)	
MOUNTING	VESA 100	
AMPLIFIED LOUDSPEAKER		

SET CONTENT

Tablet, Battery, Hand Strap, i.safe PROTECTOR 2.0 USB-C Cable, Power Adapter universal, Screwdriver, Display Protection Foil and Safety Instructions

